



INTRODUCING

# STORAGE INSTANTIATION DAEMON


PETER RAJNOHA <PRAJNOHA@REDHAT.COM>

DEVCONF.CZ, JANUARY 27 2019, BRNO

# UEVENTS OVERVIEW

# UEVENTS OVERVIEW

USER SPACE




KERNEL SPACE


# UEVENTS OVERVIEW




# UEVENTS OVERVIEW




# UEVENTS OVERVIEW



# UEVENTS OVERVIEW



# UEVENTS OVERVIEW





# UEVENTS

# UEVENTS

- uevents are **event notifications** that userspace can monitor

# UEVENTS

- uevents are **event notifications** that userspace can monitor
- both kernel and userspace can cause **uevents** to get generated
  - **kernel multicast** uevents
    - genuine
    - synthesized (writing to `/sys/.../uevent` file)
  - **userspace multicast** uevents
  - **userspace unicast** uevents

# UEVENTS

- uevents are **event notifications** that userspace can monitor
- both kernel and userspace can cause **uevents** to get generated
  - **kernel multicast** uevents
    - genuine
    - synthesized (writing to `/sys/.../uevent` file)
  - **userspace multicast** uevents
  - **userspace unicast** uevents
- uevent **environment in KEY=VALUE text format**
  - ACTION, DEVPATH, SUBSYSTEM, SEQNUM
  - more variables added by driver core, subsystems, drivers...

# UEVENTS

- uevents are **event notifications** that userspace can monitor
- both kernel and userspace can cause **uevents** to get generated
  - **kernel multicast** uevents
    - genuine
    - synthesized (writing to `/sys/.../uevent` file)
  - **userspace multicast** uevents
  - **userspace unicast** uevents
- uevent **environment in KEY=VALUE text format**
  - ACTION, DEVPATH, SUBSYSTEM, SEQNUM
  - more variables added by driver core, subsystems, drivers...
- **8 uevent action types:**
  - **ADD, CHANGE, REMOVE, MOVE**
  - ONLINE, OFFLINE, BIND, UNBIND

# UEVENTS

- uevents are **event notifications** that userspace can monitor
- both kernel and userspace can cause **uevents** to get generated
  - **kernel multicast** uevents
    - genuine
    - synthesized (writing to `/sys/.../uevent` file)
  - **userspace multicast** uevents
  - **userspace unicast** uevents
- uevent **environment in KEY=VALUE text format**
  - ACTION, DEVPATH, SUBSYSTEM, SEQNUM
  - more variables added by driver core, subsystems, drivers...
- **8 uevent action types:**
  - **ADD, CHANGE, REMOVE, MOVE**
  - ONLINE, OFFLINE, BIND, UNBIND
- all uevents sent through **netlink socket**

# UDEV

# UDEV

- **udev daemon** in userspace to support dynamic device management



# UDEV

- **udev daemon** in userspace to support dynamic device management
- **monitoring** netlink socket for uevents (*kernel* uevent type)

# UDEV

- **udev daemon** in userspace to support dynamic device management
- **monitoring** netlink socket for uevents (*kernel* uevent type)
- **processing udev rules**
  - key=value matching/writing
  - sysfs property matching/writing
  - sysctl parameter matching/writing
  - tag matching/creation
  - executing builtin or external commands, collecting output
  - **setting device node permissions**
  - **creating symlinks to device nodes**

# UDEV

- **udev daemon** in userspace to support dynamic device management
- **monitoring** netlink socket for uevents (*kernel* uevent type)
- **processing** udev rules
  - key=value matching/writing
  - sysfs property matching/writing
  - sysctl parameter matching/writing
  - tag matching/creation
  - executing builtin or external commands, collecting output
  - **setting device node permissions**
  - **creating symlinks to device nodes**
- **storing** records in udev database
  - records per device
  - subset of key=value environment sent with uevent
  - key=value pairs added by rules

# UDEV

- **udev daemon** in userspace to support dynamic device management
- **monitoring** netlink socket for uevents (*kernel* uevent type)
- **processing** udev rules
  - key=value matching/writing
  - sysfs property matching/writing
  - sysctl parameter matching/writing
  - tag matching/creation
  - executing builtin or external commands, collecting output
  - **setting device node permissions**
  - **creating symlinks to device nodes**
- **storing** records in udev database
  - records per device
  - subset of key=value environment sent with uevent
  - key=value pairs added by rules
- **regenerating uevents** including key=value pairs resulted from udev rule processing (*udev* uevent type)

# UDEV

- **udev daemon** in userspace to support dynamic device management
- **monitoring** netlink socket for uevents (*kernel* uevent type)
- **processing** udev rules
  - key=value matching/writing
  - sysfs property matching/writing
  - sysctl parameter matching/writing
  - tag matching/creation
  - executing builtin or external commands, collecting output
  - **setting device node permissions**
  - **creating symlinks to device nodes**
- **storing** records in udev database
  - records per device
  - subset of key=value environment sent with uevent
  - key=value pairs added by rules
- **regenerating uevents** including key=value pairs resulted from udev rule processing (*udev* uevent type)
- **others able to monitor** *kernel* and/or *udev* uevents

# UEVENTS + UDEV

# UEVENTS + UDEV

USER SPACE




KERNEL SPACE

# UEVENTS + UDEV







# UEVENTS + UDEV




# UEVENTS + UDEV




# UEVENTS + UDEV




# UEVENTS + UDEV




# UEVENTS + UDEV



# UEVENTS + UDEV



# UEVENTS + UDEV



# STORAGE SPECIFICS



# STORAGE SPECIFICS

- the ideal: one single-level **device usable after *ADD* uevent**

# STORAGE SPECIFICS

- the ideal: one single-level **device usable after *ADD* uevent**
- **the reality: device usable after further actions**
  - initialization sequence
  - multistep activation scheme
  - grouping
  - layering

# STORAGE SPECIFICS

- the ideal: one single-level **device usable after *ADD* uevent**
- the reality: **device usable after further actions**
  - initialization sequence
  - multistep activation scheme
  - grouping
  - layering
- **devices may contain **signatures/metadata/external configuration** that define the next layer in the stack**
  - *blkid* scan for the majority
  - *multipath -c* to detect multipath components
  - detached header location for LUKS encrypted devices
  - further additional scans by various subsystems

# PROBLEMS WITH UDEV WHILE HANDLING STORAGE DEVICES

# PROBLEMS WITH UDEV WHILE HANDLING STORAGE DEVICES

- **overloaded uevent** action type - just a *CHANGE* for lots of notifications

# PROBLEMS WITH UDEV WHILE HANDLING STORAGE DEVICES

- **overloaded uevent** action type - just a *CHANGE* for lots of notifications
- **restricted** udev rule language

# PROBLEMS WITH UDEV WHILE HANDLING STORAGE DEVICES

- **overloaded uevent** action type - just a *CHANGE* for lots of notifications
- **restricted** udev rule language
- calling **external commands** to make (even simple) decisions

# PROBLEMS WITH UDEV WHILE HANDLING STORAGE DEVICES

- **overloaded uevent** action type - just a *CHANGE* for lots of notifications
- **restricted** udev rule language
- calling **external commands** to make (even simple) decisions
- **all rules and keys are global**, any rule can overwrite values for various keys



# PROBLEMS WITH UDEV WHILE HANDLING STORAGE DEVICES

- **overloaded uevent** action type - just a *CHANGE* for lots of notifications
- **restricted** udev rule language
- calling **external commands** to make (even simple) decisions
- all **rules and keys are global**, any rule can overwrite values for various keys
- **accessing udev database** from udev rules is clunky and error-prone

# PROBLEMS WITH UDEV WHILE HANDLING STORAGE DEVICES

- **overloaded uevent** action type - just a *CHANGE* for lots of notifications
- **restricted** udev rule language
- calling **external commands** to make (even simple) decisions
- all **rules and keys are global**, any rule can overwrite values for various keys
- **accessing udev database** from udev rules is clunky and error-prone
- problems with **identification** of current state

# PROBLEMS WITH UDEV WHILE HANDLING STORAGE DEVICES

- **overloaded uevent** action type - just a *CHANGE* for lots of notifications
- **restricted** udev rule language
- calling **external commands** to make (even simple) decisions
- all **rules and keys are global**, any rule can overwrite values for various keys
- **accessing udev database** from udev rules is clunky and error-prone
- problems with **identification** of current state
- **no direct support for grouping**

# PROBLEMS WITH UDEV WHILE HANDLING STORAGE DEVICES

- **overloaded uevent** action type - just a *CHANGE* for lots of notifications
- **restricted** udev rule language
- calling **external commands** to make (even simple) decisions
- all **rules and keys are global**, any rule can overwrite values for various keys
- **accessing udev database** from udev rules is clunky and error-prone
- problems with **identification** of current state
- no direct support for **grouping**
- no standard on marking device as **ready/usable, public, private, temporarily private**

# PROBLEMS WITH UDEV WHILE HANDLING STORAGE DEVICES

- **overloaded uevent** action type - just a *CHANGE* for lots of notifications
- **restricted** udev rule language
- calling **external commands** to make (even simple) decisions
- all **rules and keys are global**, any rule can overwrite values for various keys
- **accessing udev database** from udev rules is clunky and error-prone
- problems with **identification** of current state
- no direct support for **grouping**
- no standard on marking device as **ready/usable, public, private, temporarily private**
- **amount of work** done within udevd context may not be appropriate

# PROBLEMS WITH UDEV WHILE HANDLING STORAGE DEVICES

- **overloaded uevent** action type - just a *CHANGE* for lots of notifications
- **restricted** udev rule language
- calling **external commands** to make (even simple) decisions
- all **rules and keys are global**, any rule can overwrite values for various keys
- **accessing udev database** from udev rules is clunky and error-prone
- problems with **identification** of current state
- no direct support for **grouping**
- no standard on marking device as **ready/usable, public, private, temporarily private**
- **amount of work** done within udevd context may not be appropriate
- udevd worker process **timeout** causes the process to get killed without further fallback

# PROBLEMS WITH UDEV WHILE HANDLING STORAGE DEVICES

- **overloaded uevent** action type - just a *CHANGE* for lots of notifications
- **restricted** udev rule language
- calling **external commands** to make (even simple) decisions
- all **rules and keys are global**, any rule can overwrite values for various keys
- **accessing udev database** from udev rules is clunky and error-prone
- problems with **identification** of current state
- no direct support for **grouping**
- no standard on marking device as **ready/usable, public, private, temporarily private**
- **amount of work** done within udevd context may not be appropriate
- udevd worker process **timeout** causes the process to get killed without further fallback
- scheduling separate work requires complex **synchronization** scheme

# PROBLEMS WITH UDEV WHILE HANDLING STORAGE DEVICES

- **overloaded uevent** action type - just a *CHANGE* for lots of notifications
- **restricted** udev rule language
- calling **external commands** to make (even simple) decisions
- all **rules and keys are global**, any rule can overwrite values for various keys
- **accessing udev database** from udev rules is clunky and error-prone
- problems with **identification** of current state
- no direct support for **grouping**
- no standard on marking device as **ready/usable, public, private, temporarily private**
- **amount of work** done within udevd context may not be appropriate
- udevd worker process **timeout** causes the process to get killed without further fallback
- scheduling separate work requires complex **synchronization** scheme

**UDEV IS NOT PRIMARILY DESIGNED FOR THIS!**



# PROBLEMS WITH UDEV WHILE HANDLING STORAGE DEVICES

- **overloaded uevent** action type - just a *CHANGE* for lots of notifications
- **restricted** udev rule language
- calling **external commands** to make (even simple) decisions
- all **rules and keys are global**, any rule can overwrite values for various keys
- **accessing udev database** from udev rules is clunky and error-prone
- problems with **identification** of current state
- no direct support for **grouping**
- no standard on marking device as **ready/usable, public, private, temporarily private**
- **amount of work** done within udevd context may not be appropriate
- udevd worker process **timeout** causes the process to get killed without further fallback
- scheduling separate work requires complex **synchronization** scheme

**UDEV IS NOT PRIMARILY DESIGNED FOR THIS!**

**IT'S DESIGNED TO HANDLE NODES AND SYMLINKS IN /DEV AND THEIR PERMISSIONS**

# PROBLEMS WITH UDEV WHILE HANDLING STORAGE DEVICES

- **overloaded uevent** action type - just a *CHANGE* for lots of notifications
- **restricted** udev rule language
- calling **external commands** to make (even simple) decisions
- all **rules and keys are global**, any rule can overwrite values for various keys
- **accessing udev database** from udev rules is clunky and error-prone
- problems with **identification** of current state
- no direct support for **grouping**
- no standard on marking device as **ready/usable, public, private, temporarily private**
- **amount of work** done within udevd context may not be appropriate
- udevd worker process **timeout** causes the process to get killed without further fallback
- scheduling separate work requires complex **synchronization** scheme

**UDEV IS NOT PRIMARILY DESIGNED FOR THIS!**

**IT'S DESIGNED TO HANDLE NODES AND SYMLINKS IN /DEV AND THEIR PERMISSIONS  
WHICH IT DOES JUST FINE**

# PROBLEMS WITH UDEV WHILE HANDLING STORAGE DEVICES

- **overloaded uevent** action type - just a *CHANGE* for lots of notifications
- **restricted** udev rule language
- calling **external commands** to make (even simple) decisions
- all **rules and keys are global**, any rule can overwrite values for various keys
- **accessing udev database** from udev rules is clunky and error-prone
- problems with **identification** of current state
- no direct support for **grouping**
- no standard on marking device as **ready/usable, public, private, temporarily private**
- **amount of work** done within udevd context may not be appropriate
- udevd worker process **timeout** causes the process to get killed without further fallback
- scheduling separate work requires complex **synchronization** scheme

**UDEV IS NOT PRIMARILY DESIGNED FOR THIS!**

**IT'S DESIGNED TO HANDLE NODES AND SYMLINKS IN /DEV AND THEIR PERMISSIONS**

**WHICH IT DOES JUST FINE**

**WE NEED A BIT DIFFERENT APPROACH HERE FOR OUR NEEDS!**

# PROBLEMS WITH UDEV WHILE HANDLING STORAGE DEVICES

- **overloaded uevent** action type - just a *CHANGE* for lots of notifications
- **restricted** udev rule language
- calling **external commands** to make (even simple) decisions
- all **rules and keys are global**, any rule can overwrite values for various keys
- **accessing udev database** from udev rules is clunky and error-prone
- problems with **identification** of current state
- no direct support for **grouping**
- no standard on marking device as **ready/usable, public, private, temporarily private**
- **amount of work** done within udevd context may not be appropriate
- udevd worker process **timeout** causes the process to get killed without further fallback
- scheduling separate work requires complex **synchronization** scheme


**UDEV IS NOT PRIMARILY DESIGNED FOR THIS!**

**IT'S DESIGNED TO HANDLE NODES AND SYMLINKS IN /DEV AND THEIR PERMISSIONS**


**WHICH IT DOES JUST FINE**

**WE NEED A BIT DIFFERENT APPROACH HERE FOR OUR NEEDS!**


# CHANGES




# CHANGES



# CHANGES




# CHANGES







# CHANGES




# CHANGES




# CHANGES




# CHANGES




# CHANGES




# CHANGES



# CHANGES



# CHANGES





# STORAGE INSTANTIATION

## DAEMON AND COMPONENTS

# STORAGE INSTANTIATION DAEMON AND COMPONENTS

- **sid daemon**
  - layered on top of udev
  - executes storage-specific uevent handling and processing
  - keeps its own database

# STORAGE INSTANTIATION DAEMON AND COMPONENTS

- **sid daemon**
  - layered on top of udev
  - executes storage-specific uevent handling and processing
  - keeps its own database
- **udev builtin command**
  - bridge between udev and SID with subcommands:
    - **sid active**
      - returns *active, inactive, incompatible*
    - **sid identify**
      - relays uevent with environment to SID
      - requests execution of identification and related routines
      - returns KEY=VALUE results for use in udev rules or to store in udev db
    - **sid checkpoint** <checkpoint\_name> [<key> ...]
    - **sid version**

# STORAGE INSTANTIATION DAEMON AND COMPONENTS

- **sid daemon**
  - layered on top of udev
  - executes storage-specific uevent handling and processing
  - keeps its own database
- **udev builtin command**
  - bridge between udev and SID with subcommands:
    - **sid active**
      - returns *active, inactive, incompatible*
    - **sid identify**
      - relays uevent with environment to SID
      - requests execution of identification and related routines
      - returns KEY=VALUE results for use in udev rules or to store in udev db
    - **sid checkpoint** <checkpoint\_name> [<key> ...]
    - **sid version**
- **library interface**
  - access SID's information store
  - subscribe to SID notifications

# STORAGE INSTANTIATION DAEMON AND COMPONENTS

- **sid daemon**
  - layered on top of udev
  - executes storage-specific uevent handling and processing
  - keeps its own database
- **udev builtin command**
  - bridge between udev and SID with subcommands:
    - **sid active**
      - returns *active, inactive, incompatible*
    - **sid identify**
      - relays uevent with environment to SID
      - requests execution of identification and related routines
      - returns KEY=VALUE results for use in udev rules or to store in udev db
    - **sid checkpoint** <checkpoint\_name> [<key> ...]
    - **sid version**
- **library interface**
  - access SID's information store
  - subscribe to SID notifications
- **sidctl command line interface**
  - control and access SID and its information store

# STORAGE INSTANTIATION


## DAEMON IDENTIFY STAGES



UDEVD WORKER


# STORAGE INSTANTIATION

## DAEMON IDENTIFY STAGES




# STORAGE INSTANTIATION

## DAEMON IDENTIFY STAGES







# STORAGE INSTANTIATION DAEMON IDENTIFY STAGES




# STORAGE INSTANTIATION DAEMON IDENTIFY STAGES




# STORAGE INSTANTIATION DAEMON IDENTIFY STAGES



# STORAGE INSTANTIATION DAEMON IDENTIFY STAGES




# STORAGE INSTANTIATION DAEMON IDENTIFY STAGES




# STORAGE INSTANTIATION


## DAEMON IDENTIFY STAGES



# STORAGE INSTANTIATION DAEMON IDENTIFY STAGES



# STORAGE INSTANTIATION DAEMON IDENTIFY STAGES






# SID DAEMON

## IDENTIFY - STAGE "A"


# SID DAEMON

## IDENTIFY - STAGE "A"




# SID DAEMON

## IDENTIFY - STAGE "A"




# SID DAEMON

## IDENTIFY - STAGE "A"




# SID DAEMON

## IDENTIFY - STAGE "A"




# SID DAEMON

## IDENTIFY - STAGE "A"




# SID DAEMON

## IDENTIFY - STAGE "A"



# SID DAEMON


## IDENTIFY - STAGE "A"






# SID DAEMON

## IDENTIFY - STAGE "A"




# SID DAEMON

## IDENTIFY - STAGE "A"




# SID DAEMON

## IDENTIFY - STAGE "A"




# SID DAEMON

## IDENTIFY - STAGE "A"




# SID DAEMON

## IDENTIFY - STAGE "A"




# SID DAEMON

## IDENTIFY - STAGE "A"




# SID DAEMON

## IDENTIFY - STAGE "A"



# SID DAEMON


## IDENTIFY - STAGE "A"






# SID DAEMON

## IDENTIFY - STAGE "A"




# SID DAEMON

## IDENTIFY - STAGE "A"




# SID DAEMON

## IDENTIFY - STAGE "A"




# SID DAEMON

## IDENTIFY - STAGE "A"




# SID DAEMON

## IDENTIFY - STAGE "A"




# SID DAEMON

## IDENTIFY - STAGE "A"




# SID DAEMON

## IDENTIFY - STAGE "A"



# SID DAEMON


## IDENTIFY - STAGE "A"






# SID DAEMON

## IDENTIFY - STAGE "A"



# SID DAEMON

## IDENTIFY - STAGE "A"




# SID DAEMON

## IDENTIFY - STAGE "B"


# SID DAEMON

## IDENTIFY - STAGE "B"




# SID DAEMON

## IDENTIFY - STAGE "B"




# SID DAEMON

## IDENTIFY - STAGE "B"




# SID DAEMON

## IDENTIFY - STAGE "B"



# SID DAEMON


## IDENTIFY - STAGE "B"






# SID DAEMON

## IDENTIFY - STAGE "B"




# SID DAEMON

## IDENTIFY - STAGE "B"



# SID DAEMON

## IDENTIFY - STAGE "B"



# SID DAEMON DATABASE

# SID DAEMON DATABASE

- **key-value** (KV) database with various backends

# SID DAEMON DATABASE

- **key-value** (KV) database with various backends
- **value types**
  - simple
  - vector

# SID DAEMON DATABASE

- **key-value** (KV) database with various backends
- **value types**
  - simple
  - vector
- **snapshot** separation

# SID DAEMON DATABASE

- **key-value** (KV) database with various backends
- **value types**
  - simple
  - vector
- **snapshot** separation
- **delta synchronization** of vector values



# SID DAEMON DATABASE

- **key-value** (KV) database with various backends
- **value types**
  - simple
  - vector
- **snapshot** separation
- **delta synchronization** of vector values
- **separate key namespaces**
  - **KV\_NS\_UDEV** (import/export from/to udev)
  - **KV\_NS\_GLOBAL** (visible globally)
  - **KV\_NS\_MODULE** (visible only in specific module)
  - **KV\_NS\_DEVICE** (visible only when processing specific device)

# SID DAEMON

## DATABASE

- **key-value** (KV) database with various backends
- **value types**
  - simple
  - vector
- **snapshot** separation
- **delta synchronization** of vector values
- separate **key namespaces**
  - **KV\_NS\_UDEV** (import/export from/to udev)
  - **KV\_NS\_GLOBAL** (visible globally)
  - **KV\_NS\_MODULE** (visible only in specific module)
  - **KV\_NS\_DEVICE** (visible only when processing specific device)
- per-module **protection flags**
  - **KV\_PROTECTED** (originating module can read-write, others read-only)
  - **KV\_PRIVATE** (originating module can read-write, others unable to access)
  - **KV\_RESERVED** (originating module reserves, others can't take over)

# SID DAEMON DATABASE

- **key-value** (KV) database with various backends
- **value types**
  - simple
  - vector
- **snapshot** separation
- **delta synchronization** of vector values
- separate **key namespaces**
  - **KV\_NS\_UDEV** (import/export from/to udev)
  - **KV\_NS\_GLOBAL** (visible globally)
  - **KV\_NS\_MODULE** (visible only in specific module)
  - **KV\_NS\_DEVICE** (visible only when processing specific device)
- per-module **protection flags**
  - **KV\_PROTECTED** (originating module can read-write, others read-only)
  - **KV\_PRIVATE** (originating module can read-write, others unable to access)
  - **KV\_RESERVED** (originating module reserves, others can't take over)
- **persistence**
  - **KV\_PERSISTENT** (persist record for next use)

**QUESTIONS ?**

**github:** <https://github.com/prajnoha/sid>

**freenode:** prajnoha on #lvm

**email:** prajnoha@redhat.com

# THANK YOU!



redhat.®